MASSETTO

Premium Contract Rubber Flooring

MONDO

Nov. 2025

MASSETTO

Smooth rubber surface with a concrete design.

THICKNESS	WEIGHT	ROLLS	TILES
0.118 in (3 mm)	~1.00 lb/ft² (~4.9 kg/m²)	6 ft 2 in x 32 ft 9 in (1.9 m x 10 m)	24 in x 24 in (61 cm x 61 cm)

S01 Ivory

S04 Haze

S02 Antique

S05 Cement

S03 Greige

S06 Charcoal

WITH DUAL DUROMETER TECHNOLOGY

Mondo's unique dual durometer technology is a process where the wear layer and performance layer have undergone intermolecular bonding and cannot be separated. The process not only increases the product's overall durability, it enhances performance, including acoustic and comfort benefits.

DURABILITY

UV-cured Mondoshield surface treatment
Tested for Abrasion Resistance (ASTM D3389) above industry requirements
Exceptional chemical resistance - ASTM F925
Great static and rolling load resistance
15-year standard limited wear warranty

SAFETY

Excellent Microbial Resistance
Uniform nonporous construction
Great slip resistance - ASTM D2047
Class 1 fire rated - ASTM E648

REDUCED TOTAL COST OF OWNERSHIP (TCO)

Demonstrated long life expectancy
No surface waxing required
Easy to maintain with neutral floor cleaner

COMFORT

Noise absorption qualities for improved acoustics
Impact Sound Transmission Reduction - ASTM E2179
Increased underfoot comfort with anti-fatigue properties
Superior product resiliency

ENVIRONMENTAL STEWARDSHIP

Product-Specific Type III EPD
Health Product Declaration (HPD)
100% recyclable
Made without LBC red listed ingredients
GREENGUARD Gold certified
Pre-consumer recycled content
Cradle to Cradle Certified® Silver

Website

Sustainability Credentials