





# GRANITC

Smooth rubber surface with multicolored granules.



Ť	
T	







 $-0.68 \, \text{lb}/\text{ft}^2$ (~3.3 kg/m<sup>2</sup>) TILES

WEIGHT

ESD

24 in x 24 in (61 cm x 61 cm)

# DURABILITY

UV cured MONDOshield maintenance mitigation system Proven wear abrasion resistance - ASTM D3389 High stain and chemical resistance - ASTM F925 Great static and rolling load resistance 15-year wear warranty

### COMFORT

Noise absorption qualities for improved acoustics - ISO 10140-3 Impact Sound Transmission Reduction - ASTM E2179 Increased underfoot comfort with anti-fatigue properties Superior product resiliency

## LIFE-CYCLE COST/EASE OF MAINTENANCE

Low overall cost of ownership from savings on maintenance Demonstrated long life expectancy No waxing required

#### SAFETY

Excellent fungal, bacterial and microbial resistance throughout Slip resistance - complies with ADA 302 Floor and ground surfaces Class 1 fire rated - ASTM E648 Resistance to Fungi - ASTM G21

#### **ENVIRONMENTAL STEWARDSHIP**

EPD and HPD 100% recyclable Does not contain any LBC red listed ingredient **GREENGUARD** Gold certified Meets CA section 01350 Cradle to Cradle Certified® Silver

Specs





















G370 Ice Mountain







G342 Azzuri







G315 Natural Chamois



G472 Tangelo





G378 Spring Valley



G305 Venezia  $(\mathbf{X})$ 





G306 City Storm



Sustainability Credential



#### FLOORING

