







Smooth rubber surface with a painted concrete design.





ROLLS 6 ft 2 in x 32 ft 9 in (1.9 m x 10 m) TILES 24 in x 24 in (61 cm x 61 cm)

WEIGHT ~1.00 lb/ft² (~4.9 kg/m²)

WITH DUAL DUROMETER TECHNOLOGY

MONDO's unique Dual Durometer Technology is a process through which a wear layer is molecularly bound to a bottom performance layer. It increases the durability and performance of the flooring and allows for a long-lasting appearance.

DURABILITY

UV cured MONDOshield maintenance mitigation system Proven wear abrasion resistance - ASTM D3389 High stain and chemical resistance - ASTM F925 Great static and rolling load resistance 15-year wear warranty

COMFORT

Noise absorption qualities for improved acoustics - ISO 10140-3 Impact Sound Trasmission Reduction - ASTM E2179 Increased underfoot comfort with anti-fatigue properties Superior product resiliency

LIFE-CYCLE COST/EASE OF MAINTENANCE

Low overall cost of ownership from savings on maintenance Demonstrated long life expectancy No waxing required

SAFETY

Specs

Excellent fungal, bacterial and microbial resistance throughout Slip resistance - complies with ADA 302 Floor and ground surfaces Class 1 fire rated - ASTM E648 Resistance to Funghi - ASTM G21

ENVIRONMENTAL STEWARDSHIP

HPD 100% recyclable Does not contain any LBC red listed ingredient GREENGUARD Gold certified Meets CA section 01350 2% pre-consumer recycled content 10% rapidly renewable content Cradle to Cradle Certified® Silver S01 Ivory

S02 Antique



S03 Greige







S05 Cement

S06 Charcoal

Sustainability Credential



www.mondocontractflooring.com mondo@mondocontractflooring.con 1.800.633.8138

#