







Hammered rubber surface with multicolored granules.

TILES

39 3/8 in x 39 3/8 in

(100 cm x 100 cm)





Z687 Coin


38 Dark Metal

Z676 Fog


Z675 Smoke

674 Ash














Z678 Apricot

Sustainability Credential





# DURABILITY

THICKNESS 0.138 in

(3.5 mm)

Proven wear abrasion resistance - ASTM D3389 High stain and chemical resistance - ASTM F925 Great static and rolling load resistance 15-year warranty on excessive wear

### COMFORT

Noise absorption qualities for improved acoustics - ISO 10140-3 Increased underfoot comfort with anti-fatigue properties Superior product resiliency

## LIFE-CYCLE COST/EASE OF MAINTENANCE

Low overall cost of ownership from savings on maintenance Demonstrated long life expectancy No waxing required

### SAFETY

Excellent fungal, bacterial and microbial resistance throughout Slip resistance - complies with ADA 302 Floor and ground surfaces Class 1 fire rated - ASTM E648 Resistance to Fungi - ASTM G21

**ENVIRONMENTAL STEWARDSHIP** EPD and HPD 100% recyclable Does not contain any LBC red listed ingredient **GREENGUARD** Gold certified Meets CA section 01350

Cradle to Cradle Certified® Silver

Specs















Z680 Cactus

Z672 Cinnamon









WEIGHT ~1.15 lb/ft<sup>2</sup> (~5.6 kg/m<sup>2</sup>)