ZEUS

STATIC DISSIPATIVE

Premium Contract Rubber Flooring





THICKNESS (3.5 mm)



WEIGHT ~1.15 lb/ft² $(\sim 5.6 \text{ kg/m}^2)$



TILES (100 cm x 100 cm)
















































DURABILITY

Tested for Abrasion Resistance (ASTM D3389) above industry requirements Exceptional chemical resistance - ASTM F925 Great static and rolling load resistance 15-year standard limited wear warranty

SAFETY

Excellent Microbial Resistance Uniform nonporous construction Great slip resistance - ASTM D2047 Class 1 fire rated - ASTM E648

REDUCED TOTAL COST OF OWNERSHIP (TCO)

Demonstrated long life expectancy No surface waxing required Easy to maintain with neutral floor cleaner

COMFORT

Noise absorption qualities for improved acoustics Impact Sound Transmission Reduction - ASTM E2179 Increased underfoot comfort with anti-fatigue properties Superior product resiliency

ENVIRONMENTAL STEWARDSHIP

Product-Specific Type III EPD Health Product Declaration (HPD) 100% recyclable Made without LBC red listed ingredients GREENGUARD Gold certified Pre-consumer recycled content Cradle to Cradle Certified® Silver

Z682 Navy























Sustainability Credentials