

UNI

Premium Contract Rubber Flooring

MS PRO



MONDO

NOV 2024

UNI

Smooth rubber surface in one solid color.

MS PRO



THICKNESS
0.118 in
[3 mm]



WEIGHT
~1.07 lb/ft²
[~5.2 kg/m²]



ROLLS
6 ft 2 in x 32 ft 9 in
[1.9 m x 10 m]



TILES
24 in x 24 in
[61 cm x 61 cm]



WITH DUAL DUROMETER TECHNOLOGY

Mondo's unique dual durometer technology is a process where the wear layer and performance layer have undergone intermolecular bonding and cannot be separated. The process not only increases the product's overall durability, it enhances performance, including acoustic and comfort benefits.

DURABILITY

NEW double technology (UV+Laser) MS PRO matte surface treatment

Tested for Abrasion Resistance (ASTM D3389) above industry requirements
Exceptional chemical resistance - ASTM F925
Great static and rolling load resistance
15-year standard limited wear warranty

SAFETY

Excellent Microbial Resistance
Uniform nonporous construction
Great slip resistance - ASTM D2047
Class 1 fire rated - ASTM E648

REDUCED TOTAL COST OF OWNERSHIP (TCO)

Demonstrated long life expectancy
No surface waxing required
Easy to maintain with neutral floor cleaner

COMFORT

Noise absorption qualities for improved acoustics
Impact Sound Transmission Reduction
Increased underfoot comfort with anti-fatigue properties
Superior product resiliency

ENVIRONMENTAL STEWARDSHIP

Product-Specific Type III EPD
Health Product Declaration (HPD)
100% recyclable
Made without LBC red listed ingredients
GREENGUARD Gold certified
Pre-consumer recycled content
Cradle to Cradle Certified® Silver

Website



Sustainability Credentials