

ZEUS

Premium Contract Rubber Flooring

STATIC DISSIPATIVE



 **MONDO**

MAY 2024

ZEUS

Hammered rubber surface with multicolor granules.

STATIC DISSIPATIVE




THICKNESS
0.138 in
(3.5 mm)




WEIGHT
~1.15 lb/ft²
[~5.6 kg/m²]



TILES
39 3/8 in x 39 3/8 in
(100 cm x 100 cm)




Z670 Pearl




Z676 Fog



Z669 Moon




Z687 Coin




Z685 Glacier




Z680 Cactus




Z671 Biscuit




Z675 Smoke



Z686 Statue




Z688 Slate




Z684 Sky




Z679 Citrine




Z628 Taupe




Z674 Ash




Z626 Silver City




Z681 Iron




Z683 Sapphire




Z677 Ruby




Z672 Cinnamon




Z673 Armor



Z639 Sterling



Z638 Dark Metal



Z682 Navy



Z678 Apricot

DURABILITY

- Tested for Abrasion Resistance (ASTM D3389) above industry requirements
- Exceptional chemical resistance - ASTM F925
- Great static and rolling load resistance
- 15-year standard limited wear warranty

SAFETY

- Excellent Microbial Resistance
- Uniform nonporous construction
- Great slip resistance - ASTM D2047
- Class 1 fire rated - ASTM E648

REDUCED TOTAL COST OF OWNERSHIP (TCO)

- Demonstrated long life expectancy
- No surface waxing required
- Easy to maintain with neutral floor cleaner

COMFORT

- Noise absorption qualities for improved acoustics
- Impact Sound Transmission Reduction - ASTM E2179
- Increased underfoot comfort with anti-fatigue properties
- Superior product resiliency

ENVIRONMENTAL STEWARDSHIP

- Product-Specific Type III EPD
- Health Product Declaration (HPD)
- 100% recyclable
- Made without LBC red listed ingredients
- GREENGUARD Gold certified
- Pre-consumer recycled content
- Cradle to Cradle Certified® Silver

Website



Sustainability Credentials