

Product Description

Prefabricated vulcanized rubber stair treads and risers. ASTM F2169 Type TS – Thermoset Rubber; Class II – Embossed. Matte surface, low-maintenance, available in six (6) standard solid colors.

Optional Solutions

For stair landing: Prefabricated vulcanized rubber tile. Thickness: 3.2 mm. Size: 18 1/8" x 18 1/8" (46 cm x 46 cm).

For the visually impaired: 2 in (0.50 mm) tactile indicator strips, in highly visible contrasting or non-contrasting colors.

Thickness (ASTM F386)	At tread 0.275 in (7 mm)	Weight	4': 9lb (4.08 kg)/piece	Sizes	4' x 13" (1.22 m x 0.33 m)
	At transition 0.126 po (3.2 mm)		6': 14lb (6.35 kg)/piece		6' x 13" (1.83 m x 0.33 m)
					<i>Note: Adjustable step depth between 9 1/2" and 13" to fit varying riser heights.</i>

Product Performance

Test	Characteristic	Condition(s)	Requirement*	Result**
ASTM C1028	Slip Resistance	Dry, Leather Heel	≥0.50	Compliant
ASTM C1028	Slip Resistance	Dry, Neolite Heel	≥0.60	Compliant
ASTM D2240	Durometer Hardness	Shore A Durometer	≥85	Compliant
ASTM E648	Critical Radiant Flux	-	≥0.45 W/cm ² (Class 1)	Compliant
ASTM E662	Optical Density of Smoke	-	≤450	Compliant
ASTM F925	Chemical Resistance	-	≤Slight Change	Compliant***
ASTM F970	Static Loading	250 psi	≤0.005 inch	Compliant
ASTM F1514	Heat Resistance of Color	-	≤8.0 ΔE	Compliant

*For each individual test, the manufactured product is only required to meet any applicable requirement listed in the Requirement column.

**A specific result obtained from testing during manufacturing controls and/or third-party verifications may vary between production lots, laboratories, methods and/or equipment, and as such any specific result listed in the Result column does not constitute representation or warranty as to any particular production lot. Mondo reserves the right to modify product design and/or specifications at any time without notice.

***For the complete list of chemicals tested, concentrations and contact time, please communicate with Mondo's Technical Department.

Health and the Environment

Mondostep-S is manufactured in an ISO 9001 and ISO 14001 certified plant. This product is free from red listed ingredients (2022 LBC Red List CASRN Guide). Mondostep-S complies with CDPH v1.2-2017 (California Section 01350).

Limited Material Warranty

Mondostep-S comes with a 10-year limited material warranty against manufacturing defects, a 10-year limited material warranty against excessive wear under normal usage in recommended applications, and a 5-year limited material warranty against cracking of stair nosing. For all terms and conditions, please refer to Mondo's current copy of the Limited Material Warranty for Mondostep-S. A copy of the warranty is available for download from our Web site (www.mondocontractflooring.com) or please communicate with our Technical Department (technical@mondousa.com) for information.